



Fila Industria Chimica S.p.A.

via Garibaldi, 32

I - 35018 San Martino di Lupari - Padova, Italy

tel. +39 049 946 73 00

Fax +39 049 946 07 53

fila@filachim.it - www.filachim.com



Decorated concrete Encaustic cement tiles eco treatment

Technical information for floors indoors

PRE-TREATMENT

Especially when using black and white cement tiles, it is recommended to use GROUT RELEASE after laying the tiles and before grouting! This is not an obligatory stage, but because the cement tile is very absorbent, the grout pigments can effect the cement tile seriously.

Product: Fila PRW200 pre-grouting protector ECO

-> Please try on a sample tile the grout, and clean with PS87 if the grout will go away. If not than it is necessary for sure to use this pre grouting protector.
Sorry, no test of PRW200 available yet.

FIRST CLEANING

The first cleaning is essential for a good result of the whole treatment. The first cleaning is ment to take away the construction dirt and cement residue.

Product: Fila PS87 1:5 diluted in water.

Use: 1 l for 20 m²

Equipment: Professional floor polisher (single disc with green path), water vacuum cleaner, carpet cleaner or mop.

Method: Spread, after you have swept the floor and has wetted with water, the diluted Fila PS87 (1:5 in water) about it; then clean the floor with the floor polisher or carpet cleaner. Remove the rest using the water vacuum cleaner or mop.

PROTECTION INDOORS

This treatment ensures the protection of the floor against oil- and water spots and simplifies the following ordinary maintenance. Use after grouting so the grout will be treated as well.

The ECO products are water-based and this eliminates moisture not completely from the tile floor and you can relatively quickly walk over there.

Product: Fila MP90 ECO (water-based) pure.

Use: 1 l for 20-30 m²

Equipment: brush, roller, lint-free cloth.

Method: After the initial cleaning, when the tiles are laid in adhesive glue after 24 hours or when then the tiles are laid in cement after 48 hourse, use one coat. The natural look of the tile is preserved and gives no color deepening. / intensity

As long as you do not want to deepen the intensity, use after 4 hours a second coat of the Fila MP90 ECO.

**Fila Industria Chimica S.p.A.**

via Garibaldi, 32
I - 35018 San Martino di Lupari - Padova, Italy
tel. +39 049 946 73 00
Fax +39 049 946 07 53
fila@filachim.it - www.filachim.com



COLOUR INTENSITY DEEPENING

When you want the color of the floor to get more intense (like when you wet the tile with water).

Product: Fila **SATIN** (was- satin half shiny) pure.

Use: 1 l for 20-30 m²

Equipment: brush, roller, lint-free cloth.

Method: Spend 24 hours after the second treatment this layer of wax with one coat.
After 4 hours the floor is ready to use.

MAINTENANCE

The ordinary maintenance aims to remove dirt and emits stripes. You should regularly perform the maintenance.

Product: Filacleaner / Fila satin: diluted in water depending on the degree of dirt.

Equipment: mop.

Method: Dilute in water (a half cup of detergent on five ounces of water or a couple of shoots of Fila satin. Mop the surface.

Please keep the following in mind:

The instructions provided by Fila, for the products are the result of accurate, checks carried out at the laboratory of Fila.

Nevertheless, there are factors that we cannot examine, the condition of the surface to treat, properties / surface treatment of the material that have been declared rare or not, environmental conditions, skills of the user etc.

For that reason it is recommended to **treat a trial** on a tile before performing on the tile floor. Fila guarantees the quality of its products, but is not liable for incorrect use of these.

Kismet tiles and TEGELinfo advises from this point of view in good faith and hands over the Fila instructions to you. We can therefore not be held responsible for incorrect use of the Fila products and a disappointing or even failing result.